

VFD-V

Specifications

230V Series

		230V Series											
Model Type VFD-xxxV23A		007	015	022	037	055	075	110	150	185	220	300	370
Output Rating	Applicable with the 3- ϕ motor rating (KW)	0.7	1.5	2.2	3.7	5.5	7.5	11	15	18.5	22	30	37
	Applicable with the 3- ϕ motor rating (HP)	1	2	3	5	7.5	10	15	20	25	30	40	50
	Constant Torque Output Current (A)	5.0	7.5	11	17	25	33	49	65	75	90	120	146
	Variable Torque Output Current (A)	6.25	9.4	13	21	31	41	61	81	93	112	150	182
	Rated Output Capacity kVA	1.9	2.7	4.2	6.5	9.5	12.5	19	25	29	34	46	55
Input Rating	Maximum Output Voltage (V)	Proportional to the input voltage											
	Rated Input Voltage/Frequency	200/208/220/230VAC 3 Phase, 50/60 Hz											
	Operation Voltage Range/Frequency	180~265VAC, 47~63 Hz											
	Input Current	6.4	10	14.9	21.2	25.2	33.2	58	69	83	100	120	146
	Weight (Kg)	4.7	5.5	5.7	7.7	10.5	10.5	13.5	13.5	13.5	13.5	36	36

460V Series

		460V Series														
Model Type VFD-xxxV43A		007	015	022	037	055	075	110	150	185	220	300	370	450	550	750
Output Rating	Applicable with the 3- ϕ motor rating (KW)	0.7	1.5	2.2	3.7	5.5	7.5	11	15	18.5	22	30	37	45	55	75
	Applicable with the 3- ϕ motor rating (HP)	1	2	3	5	7.5	10	15	20	25	30	40	50	60	75	100
	Constant Torque Output Current (A)	3.0	4.2	6	8.5	13	18	24	32	38	45	60	73	91	110	150
	Variable Torque Output Current (A)	3.8	5.3	7.5	10	16	22	30	40	47	56	75	91	113	138	188
	Rated Output Capacity kVA	2.3	3.2	4.6	6.5	9.9	13.7	18	24	29	34	46	56	69	84	114
Input Rating	Maximum Output Voltage (V)	Proportional to the input voltage														
	Rated Input Voltage/Frequency	380/400/415/460 VAC 3 Phase, 50/60 Hz														
	Operation Voltage Range/Frequency	340~500VAC, 47~63 Hz														
	Input Current	4.0	5.7	7.3	9.9	12.2	17.2	25	32	39	49	60	73	91	130	175
	Weight (Kg)	4.7	5.7	5.7	7.7	10.5	13.5	13.5	13.5	13.5	13.5	36	36	36	60	60

Model Explanation

VFD	007	V	23	A
				Version
				Input Voltage 23: 230V 3-Phase 43: 460V 3-Phase
				VFD-V Series
				Maximum Applicable Motor Capacity 007: (1HP) (0.75KW) ~ 750: (100HP) (75KW)
				Product Series

VFD-V

Characteristics

Control Systems	The sinusoidal wave PWM selections include: 1. vector control; 2. torque control; 3. V/F control
Torque Start-Up	Torque start-up is above 0.5 Hz 150%
Speed Control Range	1:100 (could reach 1:1000 if connects externally with PG)
Speed Control Accuracy	0.5% (could reach 0.02% if connects externally with PG)
Speed Respond Ability	5Hz (vector control reaching 30Hz)
Maximum Output Frequency (Hz)	0.00 to 600.00 Hz
Frequency	Digital command: $\pm 0.005\%$, analog command: $\pm 0.5\%$
Output Accuracy	Digital command: 0.01Hz, analog command: 1/1000 (10bit) of the maximum output frequency
Frequency Setting Resolution	Digital command: 0.01Hz, analog command: 1/1000 (10bit) of the maximum output frequency
Torque Limits	200% torque current as the maximum
Torque Accuracy	$\pm 5\%$
Accel/Decel Time	0.00~600.00/0.0~6000.0 second
V/F Curve	The 4-point desired V/F curve & the square curve
Frequency Setting Signal	+10V, $\pm 10V$, 4~20mA, pulse wave input
Power Braking	About 20%
Motor Protection	Electronic thermal relay protection
Over-Current Protection	Current control: 220% over-current protection; 300% rated current
Grounding Current-Leakage Protection	50% rated current
Over-Load Capability	Constant/Variable Torque: 150% for 60 seconds; 200% for 2 seconds
Voltage Protection	Over-voltage level: Vdc>400/800 V Low-voltage level: Vdc<200/400 V
Input Power Over-Voltage Protection	Varistor (MOV)
Over-Heat Protection	Built-in temperature sensor
Momentary Power Loss Compensation	The setting could be as long as 5 seconds
Protection Level	NEMA 1/IP20
Operation Temperature	-10°C~40°C for UL & -10°C~50°C for CE
Storage Temperature	-20°C~60°C
Humidity	Below 90% RH (non-condensing)
Vibration	If it is below 20Hz, it is 1.0G; if between 20~60 Hz, it is then 0.6G
Cooling System	Forced wind cooling (RUN, STOP)
Installation Height	If under 1,000m, be advised to stay from corrosive gasses, liquid and dust



TermoProcesos e Instrumentación, S.A. de CV.
Filósofos 301-101A Col. Tecnológico
Monterrey, NL. México ventas@termoprocessos.com
www.termoprocessos.com tpisysmx@intercable.net
52 (81) 83 59 61 30 - 52 (81) 83 59 62 29 - Fax 52 (81) 83 58 37 77



VFD

Delta VFD-V Series Flux Vector Control AC Motor Drive

Sensorless Vector Control 0.5Hz 200% Torque possible

Features

- ▶ Sensorless vector control, speed control rate: 1:100
- ▶ PG closed-loop control, speed control rate: 1:1000
- ▶ Built-in PID feedback control
- ▶ V/F, vector control, torque control and 3 position control mode
- ▶ Zero-speed that holds the torque stay at above 150%(PG)
- ▶ MODBUS communication Baud rate reaching 115200
- ▶ Soft-PWM with the carrier frequency reaching 15kHz
- ▶ Auto-Tuning motor parameter
- ▶ 4 independent S-curve/accel/decel time setting
- ▶ Dual ratings
- ▶ Sleep function and energy-saving operation



Voltage Range:
3 Phase 230V Series: 0.75~37KW(1~50HP)
3 Phase 460V Series: 0.75~75KW(1~100HP)



VFD-V series have been approved by CE and UL


WWW.TERMOPROCESOS.COM



VFD-V


The Exterior and Characteristics of the Drive

- Best with:**
- ◆ Transmission devices
 - ◆ Elevators
 - ◆ Crane
 - ◆ CNC machine center
 - ◆ Extrusion molding
 - ◆ Injection molding
 - ◆ Auto storage system




VFD-V

VFD-PU05 Digital Keypad Operation




VFD-V


Dimensions




Accessories (Optional)



T-N Curve (Sensorless Vector Control)



Basic Wiring Diagram



Dimensions

Model	W	W1	H	H1	D	D1	D2	D3	Fig
VFD007V23A VFD007V43A VFD015V23A VFD015V23A VFD022V23B VFD022V23B	150.0(5.91)	135.0(5.32)	280.0(10.24)	244.3(9.63)	-	160.2(6.31)	-	-	A
VFD037V23A VFD037V43A	150.0(5.91)	135.0(5.32)	272.1(10.72)	244.3(9.63)	-	183.7(7.24)	-	-	B
VFD055V23A VFD055V43A VFD075V23A VFD075V43A	200.0(7.88)	185.0(7.31)	323.0(12.73)	303.0(11.94)	-	183.2(7.22)	-	-	A
VFD110V23A VFD110V43A	250.0(9.84)	228.0(8.90)	403.0(15.90)	384.0(15.12)	-	205.4(8.08)	-	-	A
VFD110V43B	200.0(7.88)	185.0(7.31)	323.0(12.73)	303.0(11.94)	-	183.2(7.22)	-	-	A
VFD180V23A VFD180V43A VFD185V23A VFD185V43A VFD220V23A VFD220V43A	250.0(9.84)	228.0(8.90)	403.0(15.90)	384.0(15.12)	-	205.4(8.08)	-	-	A
VFD300V23A	370.0(14.57)	335.0(13.19)	595.0(23.43)	560.0(22.05)	-	260.0(10.24)	132.5(5.22)	18.0(0.71)	C
VFD300V43A	370.0(14.57)	335.0(13.19)	589.0(23.19)	560.0(22.05)	-	260.0(10.24)	132.5(5.22)	18.0(0.71)	C
VFD370V23A	370.0(14.57)	335.0(13.19)	595.0(23.43)	560.0(22.05)	-	260.0(10.24)	132.5(5.22)	18.0(0.71)	C
VFD370V43A VFD450V43A	370.0(14.57)	335.0(13.19)	589.0(23.19)	560.0(22.05)	-	260.0(10.24)	132.5(5.22)	18.0(0.71)	C
VFD550V43A VFD750V43A	425.0(16.73)	385.0(15.16)	680.0(25.98)	631.0(24.84)	280.0(11.02)	294.0(10.39)	130.0(5.13)	18.0(0.71)	C

*We reserve the right of this catalogue contained information change without prior notice.